End Lift Spreader T193L

For lateral handling of empty containers

Hook-on | Integrated | Terminal West | Pin-Type

1 hydraulic function

Capacity (SWL) from 1.000 kg to 8.000 kg









Rotating End Lift Spreader T193LD 360° rotation continuous

For lateral handling and turning empty containers.

Hook-on | Integrated | Terminal West | Pin-Type

2 hydraulic functions

Capacity (SWL) from 1.000 kg to 8.000 kg











KAUP- forklift spreader for container handling

KAUP Container spreaders for forklift trucks guarantee efficient handling for all container types. Whether it's a top spreader, spreader for lateral or frontal pick-up, rigid design or telescopic - KAUP spreaders can be optimally configured for almost any application.

KAUP forklift trucks spreaders ensure maximum handling performance, providing an excellent view of the container corners. This enables the operator to position the spreader quickly and accurately.

Durable and low maintaniance

- Long service life and reliable operation, as all technical components are located in well-protected areas.
- Camera systems. LED work lights.
- Highly flexible design allows handling of even damaged containers.

Options available

- Locking via twist lock, pin or hook. Hydraulic or manual locking.
- Tropical or seawater-resistant version avialble.
- Large and individual customised telescoping ranges.
- Separate (independent) sideshift.
- Reach & slew function for precise positioning.
- 270° 360° Hydraulic rotation 270° or 360° endless (Reachstacker only).

Fixed Top Lift Spreader T192E

For top handling a specified container size
(10' to 40' ISO / Sealand / special container dimensions)

- To be slipped onto forks and inverted forks | Hook-on | Integrated | Terminal West | Pin-Type
- 1 hydraulic function
- Capacity (SWL) from 1.000 kg to 45.000 kg





Top Lift Spreader T192E telescopic version

For top handling of 10' to 40' ISO / Sealand / special container dimensions

To be slipped onto forks and reversible forks | Hook-on | Integrated | Terminal West | Pin-Type

2 hydraulic functions

Capacity (SWL) from 1.000 kg to 45.000 kg









Top Lift Spreader T192E double telescopic version

For top handling of containers with customized dimensions for example; accommodation, office, construction or module containers.

To be slipped onto forks and inverted forks | Hook-on | Integrated | Terminal West | Pin-Type

2 hydraulic functions and solenoid valve

Capacity (SWL) from 1.000 kg to 12.000 kg









Fixed Side Lift Spreader T193

For lateral handling of a specified container size (10' to 40' ISO / Sealand / special container dimensions)

- Hook-on | Integrated | Terminal West | Pin-Type
- 1 hydraulic function
- Capacity (SWL) from 1.000 kg to 12.000 kg
- Optionally available with independant sideshift
- Optionally available with hydraulically adjustable bottom support





Side Lift Spreader T193 telescopic version

For lateral handling of 10' to 40' ISO / Sealand / special container dimensions

- Hook-on | Integrated | Terminal West | Pin-Type
- 2 hydraulic functions
- Capacity (SWL) from 1.000 kg to 12.000 kg
- Optionally available with independent sideshift
- Optionally available with hydraulically adjustable bottom support



